


2404

37° JIC Flare Fittings Male Connector



Reference
Aeroquip 2021
Parker Hose 0103
Parker Tube FTX
Weatherhead C5205
SAE 070102

Part No.	Tube O.D.	1 Male JIC	2 Male NPTF	C Hex	L Length	Operating Pressure
2404-02-02	1/8	5/16 - 24	1/8 - 27	7/16	1.11	6,000
2404-03-02	3/16	3/8 - 24	1/8 - 27	7/16	1.14	6,000
2404-04-02	1/4	7/16 - 20	1/8 - 27	1/2	1.22	6,000
2404-04-04	1/4	7/16 - 20	1/4 - 18	9/16	1.42	6,000
2404-04-06	1/4	7/16 - 20	3/8 - 18	3/4	1.42	6,000
2404-04-08	1/4	7/16 - 20	1/2 - 14	7/8	1.68	6,000
2404-04-12	1/4	7/16 - 20	3/4 - 14	1 1/8	1.75	5,000
2404-05-02	5/16	1/2 - 20	1/8 - 27	9/16	1.22	6,000
2404-05-04	5/16	1/2 - 20	1/4 - 18	9/16	1.42	6,000
2404-05-06	5/16	1/2 - 20	3/8 - 18	3/4	1.42	6,000
2404-06-02	3/8	9/16 - 18	1/8 - 27	5/8	1.24	6,000
2404-06-04	3/8	9/16 - 18	1/4 - 18	5/8	1.43	6,000
2404-06-06	3/8	9/16 - 18	3/8 - 18	3/4	1.43	6,000
2404-06-08	3/8	9/16 - 18	1/2 - 14	7/8	1.69	6,000
2404-06-12	3/8	9/16 - 18	3/4 - 14	1 1/8	1.75	5,500
2404-08-02	1/2	3/4 - 16	1/8 - 27	13/16	1.34	6,000
2404-08-04	1/2	3/4 - 16	1/4 - 18	13/16	1.53	6,000
2404-08-06	1/2	3/4 - 16	3/8 - 18	13/16	1.53	6,000
2404-08-08	1/2	3/4 - 16	1/2 - 14	7/8	1.79	6,000
2404-08-12	1/2	3/4 - 16	3/4 - 14	1 1/8	1.85	5,500
2404-08-16	1/2	3/4 - 16	1 - 11 1/2	1 3/8	2.05	4,500
2404-10-04	5/8	7/8 - 14	1/4 - 18	15/16	1.70	5,000
2404-10-06	5/8	7/8 - 14	3/8 - 18	15/16	1.70	5,000
2404-10-08	5/8	7/8 - 14	1/2 - 14	15/16	1.89	5,000
2404-10-12	5/8	7/8 - 14	3/4 - 14	1 1/8	1.95	5,000
2404-10-16	5/8	7/8 - 14	1 - 11 1/2	1 3/8	2.15	4,500
2404-10-24 #	5/8	7/8 - 14	1 1/2 - 11 1/2	2"	2.35	3,000
2404-12-06	3/4	1 1/16 - 12	3/8 - 18	1 1/8	1.87	5,000
2404-12-08	3/4	1 1/16 - 12	1/2 - 14	1 1/8	2.06	5,000
2404-12-12	3/4	1 1/16 - 12	3/4 - 14	1 1/8	2.06	5,000
2404-12-16	3/4	1 1/16 - 12	1 - 11 1/2	1 3/8	2.25	5,000
2404-12-20	3/4	1 1/16 - 12	1 1/4 - 11 1/2	1 11/16	2.36	5,000
2404-12-24	3/4	1 1/16 - 12	1 1/2 - 11 1/2	2"	2.46	3,000
2404-14-08 #	7/8	1 3/16 - 12	1/2 - 14	1 1/4	2.09	5,000
2404-14-12	7/8	1 3/16 - 12	3/4 - 14	1 1/4	2.09	5,000
2404-16-08	1"	1 5/16 - 12	1/2 - 14	1 3/8	2.11	4,500

Part No.	Tube O.D.	1 Male JIC	2 Male NPTF	C Hex	L Length	Operating Pressure
2404-16-12	1"	1 5/16 - 12	3/4 - 14	1 3/8	2.11	4,500
2404-16-16	1"	1 5/16 - 12	1 - 11 1/2	1 3/8	2.30	3,000
2404-16-20	1"	1 5/16 - 12	1 1/4 - 11 1/2	1 11/16	2.40	3,000
2404-16-24	1"	1 5/16 - 12	1 1/2 - 11 1/2	2"	2.51	3,000
2404-20-12 #	1 1/4	1 5/8 - 12	3/4 - 14	1 11/16	2.23	3,000
2404-20-16	1 1/4	1 5/8 - 12	1 - 11 1/2	1 11/16	2.42	3,000
2404-20-20	1 1/4	1 5/8 - 12	1 1/4 - 11 1/2	1 11/16	2.45	3,000
2404-20-24	1 1/4	1 5/8 - 12	1 1/2 - 11 1/2	2"	2.55	3,000
2404-24-16	1 1/2	1 7/8 - 12	1 - 11 1/2	2"	2.62	3,000
2404-24-20	1 1/2	1 7/8 - 12	1 1/4 - 11 1/2	2"	2.65	3,000
2404-24-24	1 1/2	1 7/8 - 12	1 1/2 - 11 1/2	2"	2.68	3,000
2404-24-32 #	1 1/2	1 7/8 - 12	2 - 11 1/2	2 1/2	2.86	2,000
2404-32-16 #	2"	2 1/2 - 12	1 - 11 1/2	2 5/8	3.02	2,000
2404-32-20 #	2"	2 1/2 - 12	1 1/4 - 11 1/2	2 5/8	3.05	2,000
2404-32-24 #	2"	2 1/2 - 12	1 1/2 - 11 1/2	2 5/8	3.18	2,000
2404-32-32	2"	2 1/2 - 12	2 - 11 1/2	2 5/8	3.11	2,000

● Available in 316 Stainless Steel

4:1 Safety Factor

Minimum Order Quantity May Apply.