


# 2706

## Bulkhead JIC Fittings Male Bulkhead Connector

Reference  
Parker Hose 0153  
Parker Tube WFTX  
SAE J514



Part No.	Tube O.D.	1 Male NPTF	2 Bulkhead Male JIC	C Hex	I Assm.	L Length	Ø W Diameter	Operating Pressure
2706-02-04 #	1/4	1/8 - 27	7/16 - 20	11/16	1.20	1.80	0.44	6,000
2706-04-04	1/4	1/4 - 18	7/16 - 20	11/16	1.20	2.03	0.44	6,000
2706-04-06	3/8	1/4 - 18	9/16 - 18	13/16	1.28	2.19	0.56	6,000
2706-06-06	3/8	3/8 - 18	9/16 - 18	13/16	1.28	2.22	0.56	6,000
2706-06-08	1/2	3/8 - 18	3/4 - 16	1"	1.44	2.42	0.75	6,000
2706-08-08	1/2	1/2 - 14	3/4 - 16	1"	1.44	2.60	0.75	6,000
2706-08-10	5/8	1/2 - 14	7/8 - 14	1 1/8	1.58	2.72	0.88	5,000
2706-12-12	3/4	3/4 - 14	1 1/16 - 12	1 3/8	1.75	2.93	1.06	5,000
2706-16-16	1"	1 - 11 1/2	1 5/16 - 12	1 5/8	1.75	3.11	1.31	4,500
2706-20-20	1 1/4	1 1/4 - 11 1/2	1 5/8 - 12	1 7/8	1.80	3.32	1.63	3,000
2706-24-24 #	1 1/2	1 1/2 - 11 1/2	1 7/8 - 12	2 1/8	1.81	3.44	1.88	3,000

For a Locknut (306) assembled on the body, just add suffix "LN" to the series number (example: 2706LN).

4:1 Safety Factor

● Available in 316 Stainless Steel

# Minimum Order Quantity May Apply.