



Reference
Aeroquip 2216
Parker Hose 0502
Parker Tube F50G
Weatherhead C3269
SAE J514

Part No.	1 Male ORB	2 Female NPTF	C Hex	L Length	Operating Pressure
6405-04-02	7/16 - 20	1/8 - 27	9/16	1.00	6,000
6405-04-04 #	7/16 - 20	1/4 - 18	3/4	1.23	6,000
6405-04-06 # #Expander	7/16 - 20	3/8 - 18	7/8	1.28	6,000
6405-05-02	1/2 - 20	1/8 - 27	5/8	0.93	6,000
6405-05-04 #	1/2 - 20	1/4 - 18	3/4	1.21	6,000
6405-06-02	9/16 - 18	1/8 - 27	11/16	1.00	6,000
6405-06-04 #	9/16 - 18	1/4 - 18	3/4	1.22	6,000
6405-06-06 #	9/16 - 18	3/8 - 18	7/8	1.28	6,000
6405-06-08 #Expander	9/16 - 18	1/2 - 14	1 1/8	1.56	5,000
6405-08-04	3/4 - 16	1/4 - 18	7/8	1.21	6,000
6405-08-06	3/4 - 16	3/8 - 18	7/8	1.28	6,000
6405-08-08 #	3/4 - 16	1/2 - 14	1 1/8	1.59	5,000
6405-08-12 # #Expander	3/4 - 16	3/4 - 14	1 3/8	1.72	4,000
6405-10-04	7/8 - 14	1/4 - 18	1"	0.81	5,000
6405-10-06	7/8 - 14	3/8 - 18	1"	1.31	5,000
6405-10-08 #	7/8 - 14	1/2 - 14	1 1/8	1.61	5,000
6405-10-12 # #Expander	7/8 - 14	3/4 - 14	1 3/8	1.71	4,000
6405-12-04 #	1 1/16 - 12	1/4 - 18	1 1/4	1.00	5,000
6405-12-06	1 1/16 - 12	3/8 - 18	1 1/4	1.50	5,000
6405-12-08	1 1/16 - 12	1/2 - 14	1 1/4	1.64	5,000
6405-12-12	1 1/16 - 12	3/4 - 14	1 3/8	1.75	4,000
6405-12-16 #	1 1/16 - 12	1 - 11 1/2	1 5/8	2.05	3,000
6405-14-08	1 3/16 - 12	1/2 - 14	1 3/8	1.52	5,000
6405-14-12	1 3/16 - 12	3/4 - 14	1 3/8	1.69	4,000
6405-16-04 #	1 5/16 - 12	1/4 - 18	1 1/2	1.10	4,000
6405-16-06	1 5/16 - 12	3/8 - 18	1 1/2	1.13	4,000
6405-16-08	1 5/16 - 12	1/2 - 14	1 1/2	1.64	4,000
6405-16-12	1 5/16 - 12	3/4 - 14	1 1/2	1.64	4,000
6405-16-16	1 5/16 - 12	1 - 11 1/2	1 5/8	1.99	3,000
6405-16-20 # #Expander	1 5/16 - 12	1 1/4 - 11 1/2	2"	2.15	2,500
6405-20-12	1 5/8 - 12	3/4 - 14	1 7/8	1.00	3,000
6405-20-16	1 5/8 - 12	1 - 11 1/2	1 7/8	1.00	3,000
6405-20-20 #	1 5/8 - 12	1 1/4 - 11 1/2	2"	2.00	2,500
6405-20-24 # #Expander	1 5/8 - 12	1 1/2 - 11 1/2	2 3/8	2.30	2,500
6405-24-12 #	1 7/8 - 12	3/4 - 14	2 1/8	1.00	3,000
6405-24-16	1 7/8 - 12	1 - 11 1/2	2 1/8	1.00	3,000

Part No.	1 Male ORB	2 Female NPTF	C Hex	L Length	Operating Pressure
6405-24-20	1 7/8 - 12	1 1/4 - 11 1/2	2 1/8	1.94	3,000
6405-24-24	1 7/8 - 12	1 1/2 - 11 1/2	2 3/8	2.16	2,500
6405-32-20 #	2 1/2 - 12	1 1/4 - 11 1/2	2 3/4	2.00	2,000
6405-32-24	2 1/2 - 12	1 1/2 - 11 1/2	2 3/4	2.00	2,000
6405-32-32 #	2 1/2 - 12	2 - 11 1/2	2 7/8	2.10	2,000

● Available in 316 Stainless Steel

4:1 Safety Factor